JET SKI® STX® 160









POWER

4-stroke, DOHC, four valves per cylinder, **Engine**

4-cylinder inline

Displacement 1,498cc

Bore x Stroke 83.0 x 69.2mm

Compression

Ratio

10.6:1

Induction Naturally aspirated

Maximum **Boost**

N/A

Cooling

Inducted water

System

Fuel System

DFI® with 60mm throttle body

Ignition

TCBI with Digital Advance

Starting System

Electric

Propulsion System

Impeller

3-blade, oval-edge stainless steel

148mm jet pump, axial-flow, single stage

PERFORMANCE

Lubrication Semi-dry sump system

Coupling Direct drive from engine

Oil Capacity 5.3 qt

Fuel Capacity 20.6 gal

Load Capacity 496 lb

Storage

Capacity

35.0 gal

DETAILS

Overall Length 124.1 in

Overall Width 46.5 in

Overall Height 45.4 in

Curb Weight 864.4 lb*

Seating **Capacity** 3

Color Choices

Crystal White/Vibrant Blue

Warranty

12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski® watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.