2024 **KLX®230 S**







POWER		Front Brakes	Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)
Engine	4-stroke single, SOHC, air-cooled	Rear Brakes	Single 220mm petal disc with single-piston caliper (and ABS)
Displacement	233cc		
Bore x Stroke	67.0 x 66.0mm	DETAILS	
Compression Ratio	9.4:1	Frame Type	Perimeter, high-tensile steel
Maximum	13.2 lb-ft @ 6,400 rpm	Rake/Trail	24.6°/3.7 in
Torque		Overall Length	81.8 in
Fuel System	DFI® with 32mm throttle body	Overall Width	33.2 in
Ignition	TCBI with Electronic Advance	Overall Height	44.8 in
Transmission	6-speed	Ground	9.4 in
Final Drive	Sealed chain	Clearance	
Electronic Rider	Anti-lock Brake System (ABS)	Seat Height	33.2 in
Aids		Curb Weight	291.0/293.2 lb* 50-State Model
PERFORMANCE		Fuel Capacity	2.0 gal
		Wheelbase	53.7 in

Front Suspension / Wheel Travel	37mm telescopic fork/7.8 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/8.7 in
Front Tire	2.75 x 21
Rear Tire	4.10 x 18

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.

Special Features

Color Choices

Warranty

ERGO-FIT®, LCD Instrumentation with Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

Lime Green, Battle Gray

12 Month Limited Warranty

Scan with camera to view videos, key features and more.



