KLX[®]230SM ABS







P	N	V	V	FI	R
	u	\mathbf{A}^{\prime}	٧ı	LI	М

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

Maximum 13.2 lb-ft @ 6,400 rpm

9.4:1

Torque

Fuel System DFI® with dual 32mm throttle bodies

Ignition TCBI with Electronic Advance

Transmission 6-speed

Final Drive Sealed chain

Electronic Rider Anti-lock Brake System (ABS)

Aids

PERFORMANCE

Front
Suspension /
Wheel Travel

Rear Suspension
/ Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.7 in

Front Tire

110/70-17

Front Brakes Single 300mm petal disc with a dual-piston caliper and ABS

Rear Brakes Single 220mm petal disc with single-piston

caliper and ABS

DETAILS

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.9°/3.0 in

Overall Length 80.1 in

Overall Width 33.2 in

Overall Height 44.2 in

Ground 8.6 in Clearance

Seat Height 33.0 in

Curb Weight 299.8/302.0 lb* 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features | ERGO-FIT®, LCD Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

Color Choices Battle Gray

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.

Rear Tire



120/70-17