## **TERYX KRX® 1000 SE**







## **POWER**

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999c

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:

Fuel System DFI® with two 50mm throttle bodies

Ignition TCBI with Electronic Advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

## DETAILS

Lighting

**Turning Radius** 

**Cargo Bed Load** 

**Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 

Capacity

Dimensions (LxWxH)

Frame Ladder type, tubular steel

20.3 ft

351 lb

781 lb

N/A

14.6 x 33.1 x 9.1 in

Overall Length 130.1 in

Overall Width 68.1 in

Overall Height 74.6 in

**Curb Weight** 1,969.1 lb\* / 1,971.3 lb\* CA Model

Wheelbase 98.8 i

Instruments Multi-function digital meter with bar-style tachometer (2

(2) LED headlights, (2) LED taillights, LED stoplight

display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning

lamp.

Additional Features Hifonics® Bluetooth®/AM/FM Audio System, WARN® VRX 45

Winch

**Color Choices** Pearl Matte Sage Green/Metallic Carbon Gray

**Warranty** 6 Month Limited Warranty

## **CAPABILITY**

Front Suspension / Wheel Travel Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in

Rear Suspension / Wheel Travel

**Front Brakes** 

**Ground Clearance** 

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

14.4 in (max), 13.7 in (std)

Fuel Capacity 10.6 gal

Scan with camera to view videos, key features and more.

