

2025

VULCAN® 900 CUSTOM



POWER	
Engine	4-stroke, 55-degree V-twin, liquid-cooled
Displacement	903cc
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Maximum Torque	58.2 lb-ft @ 3,500 rpm
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	5-speed with positive neutral finder
Final Drive	Kevlar-reinforced belt

Front Tire	80/90-21
Rear Tire	180/70-15
Front Brakes	Single 300mm hydraulic disc
Rear Brakes	Single 270mm hydraulic disc

PERFORMANCE	
Front Suspension / Wheel Travel	41mm Showa telescopic fork/5.9 in
Rear Suspension / Wheel Travel	Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in

DETAILS	
Frame Type	Semi-double cradle, high-tensile steel
Rake/Trail	33° /7.2 in
Overall Length	94.7 in
Overall Width	35.2 in
Overall Height	44.1 in
Ground Clearance	5.5 in
Seat Height	27.0 in
Curb Weight	610.8 lb*
Fuel Capacity	5.3 gal
Wheelbase	64.8 in
Color Choices	Candy Fire Red/Ebony
Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki-la.com](https://www.kawasaki-usa.com) for full product details.