2025 **KLR®650 ADVENTURE ABS**





Front Tire

CYPHER CAMO BEIGE/METALLIC MATTE CARBON GRAY

METALLIC MATTE TWILIGHT BLUE



90/90-21

POWER

			Rear Tire	130/80-17	
	Engine	4-stroke, single cylinder, DOHC	Front Brakes	Single 300mm disc with 2-piston calipers (and	
	Displacement	652cc		ABS)	
	Bore x Stroke	100.0 x 83.0mm	Rear Brakes	Single 240mm disc with single-piston caliper (and ABS)	
	Compression Ratio	9.8:1	DETAILS		
	Maximum	39.1 lb-ft @ 4,500 rpm	DLIAILS		
	Torque		Frame Type	Tubular, semi-double cradle	
	Fuel System	DFI® with 40mm throttle body	Rake/Trail	30.0°/4.8 in	
	Ignition	CDI	Overall Length	89.8 in	
	Transmission	5-speed, return shift with wet multi-disc manual clutch	Overall Width	38.2 in	
	Final Drive	Sealed chain	Overall Height	57.3/55.9 in (screen hi/lo)	
	Electronic Rider Aids	Anti-lock Brake System (ABS)	Ground Clearance	8.3 in	
			Seat Height	34.3 in	
	PERFORMANCE		Curh Weight	487 1 lb*	

ENFURMANUE

Front Suspension / Wheel Travel 41mm telescopic fork/ 7.9 in

Rear Suspension / Wheel Travel Uni-Trak[®] single shock with adjustable rebound damping and adjustable spring preload/8.0 in

Rake/Trail	30.0°/4.8 in
Overall Length	89.8 in
Overall Width	38.2 in
Overall Height	57.3/55.9 in (screen hi/lo)
Ground Clearance	8.3 in
Seat Height	34.3 in
Curb Weight	487.1 lb*
Fuel Capacity	6.1 gal
Wheelbase	60.6 in
Color Choices	Cypher Camo Beige/Metallic Matte Carbon Gray, Metallic Matte Twilight Blue
Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.