²⁰²⁵ **KLX®300SM**







POWER Engine 4-stroke single, DOHC, liquid-cooled Displacement 292cc **Bore x Stroke** 78.0 x 61.2mm DETAILS Compression 11.1:1 Ratio DFI® with 34mm Keihin throttle body **Fuel System** Ignition CDI Transmission 6-speed, return shift with wet multi-dis manual clutch **Final Drive** Chain

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted cartridge fork with adjustable compression damping / 9.1 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/ 8.1 in
Front Tire	110/70-17

Rear Tire	130/70-17
Front Brakes	Single 300mm petal disc with a dual- piston caliper
Rear Brakes	Single 240mm petal disc with single- piston caliper

	Frame Type	Semi Double Cradle
isc	Rake/Trail	25.0°/2.8 in
	Overall Length	83.3 in
	Overall Width	31.1 in
	Overall Height	44.7 in
	Ground Clearance	9.3 in
1 in	Seat Height	33.9 in
	Curb Weight	304.3 lb*
	Fuel Capacity	2.0 gal
/ 8.1	Wheelbase	56.5 in
	Color Choices	Battle Gray, Phantom Blue
	Warranty	12 Month Limited Warranty



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.