







POWER

2-stroke, single-cylinder with exhaust power valve (KIPS), liquid-cooled

Displacement 112cc

Bore x Stroke 52.5 x 51.6mm

Compression 9.9:1 (low speed) / 8.6:1 (high speed)

Fuel System 28mm Keihin carburetor

Ignition CDI with Digital Advance

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

Front Brakes Sing

Single 220mm petal disc with dual-piston

caliper

Rear Brakes Single 184mm petal disc with single-piston

caliper

PERFORMANCE

Suspension / Wheel Travel

Rear
Suspension / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in

Front Tire

20-way compression damping/10.8 in

36mm inverted telescopic cartridge fork with

DETAILS

Frame Type High-tensile steel perimeter design with subframe member

Rake/Trail 29.0°/4.3 in

Overall Length 75.6 in

Overall Width 30.1 in

Overall Height 45.3 in

Ground 13.0 in Clearance

Seat Height 34.3 in

Curb Weight 169.7 lb*

Fuel Capacity 1.32 gal

Wheelbase 51.6 in

Features

Special ERGO-FIT®

Color Choices Lime Green

Warranty Not Available

Scan with camera (to view videos, key features and more.

Rear Tire

Front



90/100-16