





P	0	W	El	R
	v			

Engine 4-stroke, single-cylinder, DOHC, liquid-cooled

Displacement 249cc

Bore x Stroke 78.0 x 52.2mm

Compression

Ratio

itio

Fuel System DFI® with 44mm Keihin throttle body and dual

injectors

14.0:2

**Ignition** Digital DC-CDI

**Transmission** 5-speed, return shift, with wet multi-disc

manual clutch and hydraulic clutch actuation

Final Drive Chain

**Electronic Rider** 

Aids

Power Modes, Kawasaki TRaction Control

(KTRC), Launch Control Mode

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

49mm Showa inverted telescopic coil-spring fork with 23-way compression damping and 20-way rebound damping /12.0 in

20 way rebound damping / iz.o ii

Rear Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and

adjustable preload/12.1 in

Front Tire 80/100-21

Rear Tire 110/100-18

Front Brakes Single semi-floating 270mm Braking petal disc with dual-piston caliper

Rear Brakes Single 240mm Braking petal disc with single-

piston caliper

## **DETAILS**

Frame Type Aluminum perimeter

Rake/Trail 27.5°/4.8 in

Overall Length 85.8 in

Overall Width 32.3 in

Overall Height 49.6 in

Ground 13.0 in

Clearance

**Seat Height** 

Curb Weight 233.2 lb\* without fuel / 243.2 lb\*

37.2 in

Fuel Capacity 1.64 gal

Wheelbase 58.5 in

**Special Features** Smartphone Connectivity via RIDEOLOGY THE

APP KX, ERGO-FIT®

**Color Choices** Lime Green

Warranty Not Available



