







## **POWER**

2-stroke, single-cylinder with exhaust power valve (KIPS), liquid-cooled

Displacement 84cc

Bore x Stroke 48.5 x 45.8mm

Compression Ratio 10.9:1 (low speed) / 9.0:1 (high speed)

Fuel System 28mm Keihin carburetor

**Ignition** CDI with Digital Advance

**Transmission** 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

Real Blakes

**Front Brakes** 

caliper

Single 220mm petal disc with dual-piston

**Rear Brakes** Single 184mm petal disc with single-piston

caliper

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

Rear
Suspension /
Suspension /
Wheel Travel

Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in

Front Tire

36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

## **DETAILS**

Frame Type High-tensile steel perimeter design with subframe member

**Rake/Trail** 29.0° /3.8 in

Overall Length 72.0 in

Overall Width 30.1 in

Overall Height 43.3 in

Ground 11.4 in Clearance

Seat Height 32.7 in

Curb Weight 164.4 lb\*

Fuel Capacity 1.32 gal

Wheelbase 49.8 in

Special ERGO-FIT® Features

**Color Choices** Lime Green

**Warranty** Not Available

Scan with camera to view videos, key features and more.

**Rear Tire** 



90/100-14