MULE™ 4010 TRANS4x4®









Drum

POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

23 amp

Ground Clearance	7.1 in
Fuel Capacity	6.3 gal
Turning Radius	12.8 ft
Cargo Bed Dimensions (LxWxH)	50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4-person)
Cargo Bed Load Capacity	800 lb (2-person) / 401 lb (4-person)
Payload Capacity	1,330 lb
Seating Capacity	2-4
Towing Capacity	1,200 lb
Lighting	(2) Halogen headlights, (2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel**

Rear Suspension /

DeDion Axle/2.8 in

Wheel Travel

Front Tires Rear Tires

23 x 11-10 23 x 11-10

Steering

Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type

Independent, mechanical drum

Front Brakes

Drum

DETAILS

Rear Brakes

Overall Length 128.5 in **Overall Width** 58.5 in **Overall Height** 75.8 in **Curb Weight** 1,587.6 lb* Wheelbase 85.2 in Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter **Color Choices** Timberline Green, Dark Royal Red Warranty Kawasaki STRONG 3-Year Limited Warranty



