## **MULE PRO-DXT™ EPS**







## **POWER**

**Engine** 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

**Maximum Torque** 38.3 lb-ft @ 2,400 rpm

**Bore x Stroke** 74.0 x 77.0mm

**Compression Ratio** 23.5:1

**Fuel System** Bosch in-line injection pump

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

**Alternator Output** 55 amp

(max)

**Wheel Travel** 

**Ground Clearance** 10.2 in

**Fuel Capacity** 7.9 gal

**Turning Radius** 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

999 lb (3-person) / 350 lb (6-person)

person)

**Cargo Bed Load** Capacity

**Dimensions (LxWxH)** 

**Payload Capacity** 1,574 lb

**Seating Capacity** 3-person (1-row), 6-person (2-row)

**Towing Capacity** 2,000 lb

Lighting (2) Halogen headlights

## **CAPABILITY**

Double wishbone/8.7 in Front Suspension / **Wheel Travel** 

**Rear Suspension /** Double wishbone/8.5 in (L)/8.7 in (R)

**Front Tires** 26 x 9-12 **Rear Tires** 26 x 11-12

**Steering** Electric Power Steering (EPS), Tilt steering

**Park Brake Type** Independent, mechanical disc

**Front Brakes** Dual disc, 2-piston caliper

**Rear Brakes** Dual disc, 1-piston caliper

## **DETAILS**

**Overall Height** 

**Overall Length** 133.3 in

**Overall Width** 64.0 in 77.6 in

**Curb Weight** 1,942.6 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

> gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

**Color Choices** Super Black

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

**Additional Features**