TERYX KRX® 1000 eS







| D | n | V | M | E | D |
|---|---|---|---|---|---|
| _ | | ľ | v | г | π |

4-stroke, DOHC, 8-valve parallel-twin, liquid cooled **Engine**

999сс Displacement

76.7 lb-ft @ 7,000 rpm Maximum Torque

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

DFI® with (2) 50mm throttle bodies **Fuel System**

TCBI with Electronic Advance Ignition

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and

KECS controlled compression damping/18.6 in

Rear Suspension / Wheel Travel

4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully

adjustable preload, and KECS controlled compression

damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Electric Power Steering (EPS) / rack-and-pinion Steering

Front Brakes Dual hydraulic discs with 2-piston calipers

Dual hydraulic discs with single-piston calipers **Rear Brakes**

Ground Clearance 14.4 in (max), 14.0 in (std)

10.6 gal **Fuel Capacity**

Turning Radius 20.3 ft

14.6 x 33.1 x 9.1 in **Cargo Bed Dimensions** (LxWxH)

Cargo Bed Load

351 lb Capacity

Payload Capacity 781 lb

Seating Capacity

Towing Capacity N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

DETAILS

Ladder type, tubular steel Frame

Overall Length 132.1 in **Overall Width** 68.1 in **Overall Height** 77.0 in

Curb Weight 1.944.8 lb* / 1.947.0 lb* CA Model

Wheelbase 98.8 in

Multi-function digital meter with bar-style tachometer (2 Instruments

> display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

lamp, and CVT belt warning lamp

Additional Features KQR™ Sport Roof, Front Bumper, Steel skid-plates w/ drain

holes, TFT Full-Color Instrumentation with Smartphone

Connectivity

Color Choices Matte Whitish Sand Beige/Metallic Flat Raw Graystone

6 Month Limited Warranty Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.