

2025

# Z H2 SE ABS

**Kawasaki**

Let the Good Times Roll®



METALLIC MATTE GRAPHENESTEEL GRAY/EBONY/  
MIRROR COATED BLACK



## POWER

<b>Engine</b>	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled, supercharged
<b>Displacement</b>	998cc
<b>Bore x Stroke</b>	76.0 x 55.0mm
<b>Compression Ratio</b>	11.2:1
<b>Maximum Horsepower</b>	197.0 hp <sup>1</sup> @ 10,500 rpm
<b>Maximum Torque</b>	101.0 lb-ft @ 8,500 rpm
<b>Fuel System</b>	DFI® with 40mm throttle bodies; Kawasaki Supercharger
<b>Ignition</b>	TCBI with Digital Advance
<b>Transmission</b>	6-speed, return shift, dog-ring
<b>Final Drive</b>	Sealed chain
<b>Electronic Rider Aids</b>	Economical Riding Indicator, Kawasaki Electronic Control Suspension (KECS) with Showa Skyhook Technology, Kawasaki Cornering Management Function (KCMF), Power Modes, Kawasaki Launch Control Mode (KLCM), Kawasaki Traction Control (KTRC), Kawasaki Engine Brake Control (KEBC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Kawasaki Quick Shifter (KQS) (upshift & downshift), Electronic Cruise Control, IMU-Enhanced Chassis Orientation Awareness

<b>Rear Suspension / Wheel Travel</b>	Uni-Trak®, Showa gas-charged shock with KECS-controlled compression and rebound damping, manual spring preload adjustability/5.3 in
<b>Front Tire</b>	120/70-17
<b>Rear Tire</b>	190/55-17
<b>Front Brakes</b>	Dual 320mm discs with radial-mount Brembo M4.32 Calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
<b>Rear Brakes</b>	Single 260mm disc with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

## DETAILS

<b>Frame Type</b>	Trellis, high tensile steel
<b>Rake/Trail</b>	24.9° / 4.1in
<b>Overall Length</b>	82.1 in
<b>Overall Width</b>	31.9 in
<b>Overall Height</b>	44.5 in
<b>Ground Clearance</b>	5.5 in
<b>Seat Height</b>	32.7 in
<b>Curb Weight</b>	531.4 lb*
<b>Fuel Capacity</b>	5.0 gal
<b>Wheelbase</b>	57.3 in
<b>Special Features</b>	Supercharged engine, All-digital TFT color Instrumentation, All-LED lighting, Smartphone Connectivity via RIDEOLGY THE APP
<b>Color Choices</b>	Metallic Matte Graphenesteel Gray/Ebony/Mirror Coated Black
<b>Warranty</b>	12 Month Limited Warranty

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	43mm Showa SFF-BP inverted fork with KECS-controlled rebound and compression damping, manual spring preload adjustability/4.7 in
--	--

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.  
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.  
 Specifications subject to change. Visit [Kawasaki-la.com](http://Kawasaki-la.com) for full product details.