





METALLIC SPARK BLACK/GREEN



METALLIC MATTE DARK GRAY/METALLIC SPARK BLACK



## **POWER**

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled

Displacement 649cc

Bore x Stroke 83.0 x 60.0mm

10 8.1

Compression

**Ratio** 

Maximum Horsepower 67.0 hp<sup>1</sup> @ 8,000 rpm

**Maximum Torque** 

48.5 lb-ft @ 6,700 rpm

Fuel System

DFI® with Keihin 36mm throttle bodies

Ignition

TCBI with Electronic Advance

**Transmission** 

6-speed, return shift

**Final Drive** 

Sealed chain

**Electronic Rider** 

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock Brake System

Horizontal back-link with adjustable preload,

(ABS)

## **PERFORMANCE**

Front Suspension / Wheel Travel

41mm telescopic fork/4.9 in

Rear Suspension / Wheel Travel

swingarm/5.1 in

**Front Tire** 

120/70-17

**Rear Tire** 160/60-17

Front Brakes Dual 300mm petal-style discs with two-piston

calipers (and ABS)

Rear Brakes Single 220mm petal-style disc (and ABS)

## **DETAILS**

Frame Type Trellis, high tensile steel

Rake/Trail 24.0°/3.9 in

Overall Length 80.9 in

Overall Width 30.1 in

Overall Height 41.9 in

**Ground Clearance** 5.1 in

Seat Height 31.1 in

Estimated Dry 381.5 lb\*\* (ABS) / 379.3 lb\*\* (non-ABS) 50-State

Weight Model

Curb Weight 414.5 lb\* (ABS) / 412.3 lb\* (non-ABS) 50-State Model

Fuel Capacity 4.0 gal

Wheelbase 55.5 in

Special Features 4.3" All-digital TFT color Instrumentation,

Smartphone Connectivity via RIDEOLOGY THE APP

Color Choices Metallic Matte Dark Gray/Metallic Spark Black,

Metallic Spark Black/Green

**Warranty** 12 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.