BRUTE FORCE® 750 SE EPS









POWER

Engine 4-stroke, V-twin, SOHC, liquid-cooled

749cc Displacement

85.0 x 66.0mm **Bore x Stroke**

Compression Ratio

Maximum Horsepower 50.0 hp1 @ 6,750 rpm

Maximum Torque 42.8 lb-ft @ 4,750 rpm

DFI® with two 34mm throttle bodies **Fuel System**

Ignition Digital DC-CDI

Automatic Continuously Variable Transmission (CVT) with **Transmission**

(H,L,N,R)

Final Drive Selectable 2WD/4WD with variable control front differential lock,

CAPABILITY

Front Suspension /

Wheel Travel

Rear Suspension / Wheel Travel

Front Tires

Rear Tires

Front Brakes

Rear Brakes

Ground Clearance

Starting System

Fuel Capacity

Double wishbone, adjustable spring preload/6.9 in

Double wishbone, adjustable spring preload/7.4 in

AT 25 x 8-12

AT 25 x 10-12

Dual hydraulic 176mm discs with 2-piston calipers

Sealed, oil-bathed, multi-disc with independent park brake

Specifications subject to change. Visit Kawasaki-la.com for full product details.

8.7 in/9.6 in (max preload)

Electric

5.0 gal

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Turning Radius 10.5 ft

Towing Capacity 1,250 lb 264.5 lb

Total Rack Capacity Rack Capacity, Front/ 88.0/176.0 lb

Rear

Lighting All-LED lighting

DETAILS

Frame Type Double-cradle, high-tensile tubular steel

Tread Width 37.0/35.6 in

Overall Length 88.4 in

Overall Width 46.7 in

Overall Height 47.8 in

Seat Height 35.2 in

Estimated Dry Weight 723.2 lb**

Curb Weight 769.5 lb*

Wheelbase 50.6 in

Instruments Digital speedometer, 2WD/4WD drive indicator, fuel gauge,

odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder,

high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and battery voltage)

Special Features WARN® VRX 25-S Powersport Winch, Front brush guard, Hand

guards, Full-color TFT Instrumentation w/ Smartphone Connectivity via RIDEOLOGY THE APP POWERSPORTS, KQR™

Color Choices Metallic Gold Sparkle Deep Green

12 Month Limited Warranty Warranty

Scan with camera to view videos, key features and more



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. © 2025 Kawasaki Motors Corp., U.S.A.