

2026

KLX[®]140R F



- LIME GREEN
- BRIGHT WHITE



POWER

Engine	4-stroke, single-cylinder, SOHC, air-cooled
Displacement	144cc
Bore x Stroke	58.0 x 54.4mm
Compression Ratio	9.5:1
Fuel System	Keihin PB20 carburetor
Ignition	Digital DC-CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

PERFORMANCE

Front Suspension / Wheel Travel	33mm telescopic fork/7.5 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with piggyback reservoir, 20-way rebound damping and threaded preload adjustability/7.9 in
Front Tire	2.75 x 21
Rear Tire	4.10 x 18

Front Brakes	Single 220mm petal disc with a dual-piston caliper
Rear Brakes	Single 186mm petal disc with single-piston caliper

DETAILS

Frame Type	High-tensile steel, box-section perimeter
Rake/Trail	27.0° /4.6 in
Overall Length	78.9 in
Overall Width	31.1 in
Overall Height	44.7 in
Ground Clearance	12.4 in
Seat Height	33.9 in
Estimated Dry Weight	205.0 lb**
Curb Weight	218.2 lb*
Fuel Capacity	1.5 gal
Wheelbase	52.4 in
Color Choices	Lime Green, Bright White
Warranty	6 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki-la.com](https://www.kawasaki-la.com) for full product details.