## **ALL-NEW 2026**

## KLX<sup>®</sup>230 DF ABS







D	N	V	N	F	P
Г		N	w		П

**Engine** 4-stroke single, SOHC, air-cooled

**Displacement** 233cc

**Bore x Stroke** 67.0 x 66.0mm

Compression

**Ratio** 

9.4:1

Maximum

Horsepower

17.0 hp1 @ 8,000 rpm

**Maximum Torque** 

13.3 lb-ft @ 6,400 rpm

**Fuel System** 

DFI® with 32mm throttle body

Ignition

TCBI with Electronic Advance

Transmission

6-speed

**Final Drive** 

Sealed chain

## **PERFORMANCE**

Front Suspension / Wheel Travel	37mm telescopic fork/7.9 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	2.75 x 21
Rear Tire	4.10 x 18

**Front Brakes** Single 265mm petal disc with a dual-piston caliper **Rear Brakes** Single 220mm petal disc with single-piston

## **DETAILS**

**Frame Type** High-tensile steel, perimeter

9.4 in

Rake/Trail 24.6°/3.8 in

**Overall Length** 81.9 in

**Overall Width** 36.2 in

**Overall Height** 45.3 in

Ground Clearance

**Seat Height** 33.3 in

**Dry Weight** 284.4 lb\*\*

**Curb Weight** 302.1 lb\*

**Fuel Capacity** 2.0 gal

Wheelbase 53.7 in

**Special Features** ERGO-FIT®, Aluminum skid plate, Engine guards,

Hand guards, All-digital Instrumentation with

**Smartphone Connectivity** 

**Color Choices** Medium Cloudy Gray

Scan with camera to view videos, key features and more.



Specifications subject to change. Visit Kawasaki-la.com for full product details.