ALL-NEW 2026

KLX[®]230 SHERPA S ABS







POWER

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Maximum Horsepower 17.0 hp1 @ 8,000 rpm

Maximum Torque

13.3 lb-ft @ 6,400 rpm

Fuel System

DFI® with 32mm throttle body

Ignition

TCBI with Electronic Advance

Transmission

6-speed

Final Drive

Sealed chain

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/6.2 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/6.6 in
Front Tire	2.75 x 21
Rear Tire	4.10 x 18

Front Brakes Single 265mm petal disc with a dual-piston caliper

Rear Brakes Single 220mm petal disc with single-piston

DETAILS

Frame Type High-tensile steel, perimeter

24.4°/3.8 in Rake/Trail

Overall Length 81.1 in

Overall Width 36.2 in

Overall Height 44.3 in

Ground Clearance

32.5 in

8.5 in

Estimated Dry

Weight

Seat Height

282.2 lb** / 284.3 lb** 50-State Model

Curb Weight 297.7 lb* / 299.9 lb* 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.3 in

ERGO-FIT®, Even lower seat height, Aluminum **Special Features**

skid plate, Hand guards, All-digital

Instrumentation with Smartphone Connectivity

Color Choices Whitish Beige

Scan with camera to view videos, key features and more.



Specifications subject to change. Visit Kawasaki-la.com for full product details.