
KLX®300SM









Single 300mm petal disc with a dual-piston

Single 240mm petal disc with single-piston

D	N	١	A		D
Г	u	ľ	ľ	E	π

Engine 4-stroke, single-cylinder, DOHC, liquid-cooled

Displacement 292cc

Bore x Stroke 78.0 x 61.2mm

11.1:1

Compression

Ratio

Maximum Horsepower 25.0 hp¹ @ 8,000 rpm

Maximum Torque

17.7 lb-ft @ 7,000 rpm

Fuel System

DFI® with 34mm Keihin throttle body

Ignition

CDI

Transmission

6-speed, return shift with wet multi-disc manual

clutch

Final Drive Chain

DETAILS

Rear Tire

Front Brakes

Rear Brakes

Frame Type Tubular, semi-double cradle

130/70-17

caliper

caliper

Rake/Trail 25.0°/2.8 in

Overall Length 83.3 in

Overall Width 31.1 in

Overall Height 44.7 in

Ground Clearance 9.3 in

Seat Height

Estimated Dry

Weight

33.9 in 286.6 lb**

Curb Weight 304.3 lb*

Fuel Capacity 2.0 gal

Wheelbase

Color Choices

Neon Green/Ebony, Battle Gray/Ebony

Warranty 12 Month Limited Warranty

56.5 in

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted cartridge fork with adjustable compression damping/9.1 in

Rear Suspension / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with adjustable rebound damping and

spring preload/8.1 in

Front Tire

110/70-17



