







Single semi-floating 270mm Braking/Sunstar petal disc with Brembo master cylinder and dual-

Single 240mm Braking/Sunstar petal disc with

POWER

Engine 4-stroke, single-cylinder, DOHC, liquid-cooled

Displacement 449cc

96.0 x 62.1mm

Compression

Bore x Stroke

Ratio

12.5:1

Fuel System DFI® with 44mm Keihin throttle body

Ignition Digital CDI with handlebar-controlled power

modes

Transmission 5-speed, return shift, with wet multi-disc manual

clutch and hydraulic clutch actuation

Final Drive Chain

Electronic Rider

Aids

Power Modes, Kawasaki TRaction Control (KTRC),

Launch Control Mode

DETAILS

Rear Brakes

Front Tire

Rear Tire

Front Brakes

Frame Type Aluminum perimeter

80/100-21

120/80-19

piston caliper

single-piston caliper

Rake/Trail 26.6°/4.5 in

Overall Length 85.8 in

Overall Width 32.3 in

Overall Height 50.0 in

Ground Clearance 13.6 in

Seat Height 37.8 in

Curb Weight 238.3 lb* without fuel / 248.2 lb*

Fuel Capacity 1.64 gal

Wheelbase 58.3 in

Special Features | Smartphone Connectivity via RIDEOLOGY THE APP

KX™, ERGO-FIT®

Color Choices Lime Green

Warranty Not Available

PERFORMANCE

Front Suspension / Wheel Travel

49mm Showa inverted telescopic coil-spring fork with 21-way adjustable compression and 22-way adjustable rebound damping/12.0 in

Rear Suspension / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with adjustable dual-range compression damping (19-way low speed and 4.25 turn stepless high speed), 23-way adjustable rebound damping and stepless adjustable preload/12.1 in



