

NEW 2026

KX™ 85 L



POWER

Engine	2-stroke, single-cylinder with exhaust power valve (KIPS), liquid-cooled
Displacement	84cc
Bore x Stroke	48.5 x 45.8mm
Compression Ratio	10.9:1 (low speed) / 9.0:1 (high speed)
Fuel System	28mm Keihin carburetor
Ignition	CDI with digital advance
Transmission	6-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	90/100-16
Front Brakes	Single 240mm petal disc with dual-piston caliper
Rear Brakes	Single 220mm petal disc with single-piston caliper

DETAILS

Frame Type	Perimeter, high-tensile steel
Rake/Trail	29.2° / 4.6 in
Overall Length	76.2 in
Overall Width	31.5 in
Overall Height	45.9 in
Ground Clearance	13.0 in
Seat Height	34.1 in
Curb Weight	164.5 lb* without fuel / 172.4 lb*
Fuel Capacity	1.32 gal
Wheelbase	51.6 in
Special Features	ERGO-FIT®
Color Choices	Lime Green

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted fork with adjustable compression and rebound damping/10.8 in
Rear Suspension / Wheel Travel	Uni-Trak® single shock with adjustable dual-range (high-low-speed) compression and rebound damping, plus adjustable spring preload/12.0 in
Front Tire	70/100-19

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki-la.com](https://www.kawasaki-usa.com) for full product details.