MULE PRO-DXT™ EPS









POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Horsepower 24.0 hp¹ @ 3,600 rpm

Maximum Torque 38.3 lb-ft @ 2,400 rpm

Bore x Stroke 74.0 x 77.0mm

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Yes

Alternator Output 55 amp

(max)

Ground Clearance 10.2 in Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed Dimensions 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)

(LxWxH)

Cargo Bed Load

Capacity

999 lb (3-person) / 350 lb (6-person)

Payload Capacity 1,574 lb

Seating Capacity 3-person (1-row), 6-person (2-row)

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights

CAPABILITY

Front Suspension / Dou Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 in (L)/8.7 in (R)

Front Tires

26 x 9-12

Rear Tires 26 x 11-12

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, mechanical disc
Front Brakes Dual disc, 2-piston caliper

Rear Brakes Dual disc, 1-piston caliper

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Estimated Dry Weight 1,898.5 lb**

Curb Weight 1,984.5 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

Additional Features

Roof, Horn, Universal Key, High Visibility Orange Seatbelts

Color Choices Super Black

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.