

2026

MULE PRO-FX™ 1000 HD EDITION

Kawasaki

Let the Good Times Roll®



| POWER | | Ground Clearance | |
|---------------------------------|---|------------------------------|---|
| Engine | 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas | Fuel Capacity | 11.9 in (max), 11.8 in (std) |
| Displacement | 999cc | Turning Radius | 7.9 gal |
| Maximum Horsepower | 70.0 hp¹ @ 6,500 rpm | Cargo Bed Dimensions (LxWxH) | 16.0 ft |
| Maximum Torque | 61.5 lb-ft @ 4,500 rpm | Cargo Bed Load Capacity | 54.1 x 53.3 x 11.0 in |
| Bore x Stroke | 92.0 x 75.1mm | Payload Capacity | 999/600 lb CA Model |
| Compression Ratio | 10.1:1 | Seating Capacity | 1,616.3/1,263.5 lb CA Model |
| Fuel System | DFI® with 38mm throttle body | Towing Capacity | 3 |
| Transmission | Continuously Variable Transmission (CVT) with (H,L,N,R) | Lighting | 2,000 lb |
| Final Drive | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock | | (2) Halogen headlights, (2) LED headlights |
| Engine Braking | Yes | DETAILS | |
| Alternator Output (max) | 90 amp | Overall Length | 136.6 in |
| CAPABILITY | | Overall Width | 64.0 in |
| Front Suspension / Wheel Travel | Double wishbone/11.0 in | Overall Height | 81.1 in |
| Rear Suspension / Wheel Travel | Double wishbone/10.1 in | Estimated Dry Weight | 1,830.2/1,832.4 lb** CA Model |
| Front Tires | 26 x 9-12, radial | Curb Weight | 1,913.9/1,916.1 lb* CA Model |
| Rear Tires | 26 x 11-12, radial | Wheelbase | 92.3 in |
| Steering | Rack-and-pinion | Instruments | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps |
| Park Brake Type | Independent, mechanical disc | Wheel Type | Steel |
| Front Brakes | Dual disc, 2-piston caliper | Additional Features | Roof, Rear Bumper, Additional Under Seat Storage Bin, Rearview Mirror, Hydraulic Cargo Bed Lift, Self-Leveling Rear Suspension, Anti-cinch Seatbelts |
| Rear Brakes | Dual disc, 1-piston caliper | Color Choices | Firecracker Red |

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki-la.com](https://www.kawasaki-usa.com) for full product details.