

2026

MULE PRO-MX™ EPS



- GRAY
- FIRECRACKER RED



POWER		Rear Brakes	
Engine	4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled	Ground Clearance	Dual disc, 1-piston caliper
Displacement	695cc	Fuel Capacity	10.6 in
Maximum Horsepower	44.0 hp ¹ @ 6,000 rpm	Turning Radius	9.5 gal
Maximum Torque	42.7 lb-ft @ 5,000 rpm	Cargo Bed Dimensions (LxWxH)	14.0 ft
Bore x Stroke	102.0 x 85.0mm	Cargo Bed Load Capacity	33.4 x 44.1 x 9.1 in
Compression Ratio	10.3:1	Payload Capacity	699 lb / 600 lb CA Model
Fuel System	DFI® with 44mm throttle body	Seating Capacity	1,200 lb / 1,100 lb CA Model
Transmission	Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R)	Towing Capacity	2
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Lighting	1,500 lb
Engine Braking	Yes	DETAILS	
Alternator Output (max)	35.7 amp		
CAPABILITY		Overall Length	110.0 in
Front Suspension / Wheel Travel	Double wishbone/8.6 in	Overall Width	60.0 in
Rear Suspension / Wheel Travel	Double wishbone/9.1 in	Overall Height	74.4 in
Front Tires	25 x 8-12, radial	Estimated Dry Weight	1,512.6 lb** / 1,514.8 lb** CA Model
Rear Tires	25 x 10-12, radial	Curb Weight	1,587.6 lb* / 1,589.8 lb* CA Model
Steering	Electric Power Steering (EPS), Tilt steering	Wheelbase	78.9 in
Park Brake Type	Independent, mechanical disc	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps
Front Brakes	Dual disc, 2-piston caliper	Color Choices	Gray, Firecracker Red
		Warranty	Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki-usa.com](https://www.kawasaki-usa.com) for full product details.