NINJA® 1100SX SE ABS









POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 1.099cc

Bore x Stroke 77.0 x 59.0mm

Compression Ratio 11.8:1

Maximum 134.0 hp1 @ 9,000 rpm Horsepower

Maximum Torque 83.2 lb-ft @ 7,600 rpm

Fuel System DFI® with 38mm Electronic Throttle Valves

Ignition TCBI with Digital Advance

6-speed, return shift with wet multi-disc manual Assist & **Transmission**

Slipper Clutch

Final Drive Sealed chain

Electronic Rider Aids Economical Riding Indicator, Electronic Cruise Control,

Kawasaki TRaction Control (KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-

Enhanced Chassis Orientation Awareness

PERFORMANCE

Front Suspension / **Wheel Travel**

41mm inverted telescopic Showa fork with compression and rebound damping, adjustable spring preload/4.7 in

Rear Suspension / **Wheel Travel**

Horizontal back-link, Öhlins S46 gas-charged rear shock with rebound damping, remotely adjustable spring

preload/5.6 in

Front Tire 120/70-17

Rear Tire 190/50-17

Front Brakes Dual 300mm discs with radial-mount 4-piston Brembo

M4.32 monobloc calipers, Kawasaki Intelligent anti-lock

Brake System (KIBS)

Rear Brakes Single 260mm disc with single-piston caliper, Kawasaki

Intelligent anti-lock Brake System (KIBS)

DETAILS

Frame Type Twin-spar aluminum

24.0°/3.9 in Rake/Trail **Overall Length** 82.7 in

Overall Width 31.7 in

Overall Height 46.9 in/48.2 in w/ windshield high

Ground Clearance 5.3 in

Seat Height 32.3 in

469.7 lb** **Estimated Dry**

Weight

Curb Weight 516.0 lb*

Fuel Capacity 5.0 gal

Wheelbase 56.7 in

Special Features 4.3" All-digital TFT Instrumentation, All-LED lighting, USB

Type-C outlet, Grip heaters, Smartphone Connectivity with available Voice Command via RIDEOLOGY THE APP

MOTORCYCLE***

Color Choices Metallic Deep Blue/Metallic Diablo Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). *RIDEOLOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.

1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.