

2027

BRUTE FORCE® 750 SE EPS

Kawasaki

Let the Good Times Roll®



 METALLIC GOLD SPARKLE DEEP GREEN



POWER

Engine	4-stroke, V-twin, SOHC, liquid-cooled
Displacement	749cc
Bore x Stroke	85.0 x 66.0mm
Compression Ratio	9.3:1
Maximum Horsepower	50.0 hp ¹ @ 6,750 rpm
Maximum Torque	42.8 lb-ft @ 4,750 rpm
Fuel System	DFI® with two 34mm throttle bodies
Ignition	Digital DC-CDI
Transmission	Automatic Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD with variable control front differential lock, shaft

CAPABILITY

Front Suspension / Wheel Travel	Double wishbone, adjustable spring preload/6.9 in
Rear Suspension / Wheel Travel	Double wishbone, adjustable spring preload/7.4 in
Front Tires	AT 25 x 8-12
Rear Tires	AT 25 x 10-12
Front Brakes	Dual hydraulic 176mm discs with 2-piston calipers
Rear Brakes	Sealed, oil-bathed, multi-disc with independent park brake
Ground Clearance	8.7 in/9.6 in (max preload)
Starting System	Electric
Fuel Capacity	5.0 gal

Steering	Rack-and-pinion w/ Electric Power Steering (EPS)
Turning Radius	10.5 ft
Towing Capacity	1,250 lb
Total Rack Capacity	264.5 lb
Rack Capacity, Front/Rear	88.0/176.0 lb
Lighting	All-LED lighting

DETAILS

Frame Type	Double-cradle, high-tensile tubular steel
Tread Width	37.0/35.6 in
Overall Length	88.4 in
Overall Width	46.7 in
Overall Height	47.8 in
Seat Height	35.2 in
Estimated Dry Weight	723.2 lb**
Curb Weight	769.5 lb*
Wheelbase	50.6 in
Instruments	Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and battery voltage)
Special Features	2,500-lb winch with synthetic rope, Front brush guard, Hand guards, Full-color TFT Instrumentation w/ Smartphone Connectivity via RIDELOGY THE APP POWERSPORTS, KQR™ system
Color Choices	TRUETIMBER® STRATA
Warranty	12 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. © 2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki-la.com for full product details.