

ACTUALIZADA 2025

MULE PRO-FXT™ 820 EPS

Kawasaki
Let the Good Times Roll®



 VERDE TIMBERLINE



POTENCIA

| | |
|-------------------------|---|
| Motor | 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas |
| Cilindrada | 812cc |
| Par motor máximo | 48.0 lb-ft @ 3,500 rpm |
| Diámetro por carrer | 72.0 x 66.5mm |
| Relación de compresión | 9.5:1 |
| Sistema de combustible | DFI® with 34mm throttle body |
| Transmisión | Continuously Variable Transmission (CVT) with (H,L,N,R) |
| Transmisión final | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| Frenado del motor | Yes |
| Alternator Output (max) | 75 amp |

| | |
|---|---|
| Frenos traseros | Dual disc, 1-piston caliper |
| Distancia al suelo | 10.2 in |
| Depósito de combustible | 7.9 gal |
| Radio de giro | 16.0 ft |
| Dimensiones de la plataforma de carga (L x An x Al) | 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person) |
| Capacidad de la plataforma de carga | 999 lb (3-person)/350 lb (6-person)/348 lb CA Model |
| Capacidad de carga útil | 1,616.3/1,263.5 lb CA Model |
| Asientos | 3-person (1 row), 6 person (2 row) |
| Capacidad de remolque | 2,000 lb |
| Faros | (2) Halogen headlights |

CAPACIDAD

| | |
|---|---|
| Suspensión delantera/ recorrido del neumático | Double wishbone/8.7 in |
| Suspensión trasera/ recorrido del neumático | Double wishbone/8.5 in (L)/8.7 in (R) |
| Neumáticos delanteros | 26 x 9-12, radial |
| Neumáticos traseros | 26 x 11-12, radial |
| Wheel Type | Steel |
| Dirección | Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering |
| Tipo de freno de estacionamiento | Independent, mechanical disc |
| Frenos delanteros | Dual disc, 2-piston caliper |

DETALLES

| | |
|-------------------------|---|
| Largo total | 133.3 in |
| Ancho total | 64.0 in |
| Altura total | 77.6 in |
| Dry Weight | 1,832.4/1,834.6 lb** CA Model |
| Peso en orden de marcha | 1,911.7/1,913.9 lb* CA Model |
| Distancia entre ejes | 92.3 in |
| Instrumental | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps |
| Colores disponibles | Timberline Green |
| Garantía | Garantía limitada Kawasaki Strong de 3 años |

Escanear con cámara para ver videos, características clave y más.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
 **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
 All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visite Kawasaki-la.com para obtener detalles completos del producto.