

ACTUALIZADA 2025

# MULE PRO-FXT™ 820 EPS

**Kawasaki**  
Let the Good Times Roll®



 VERDE TIMBERLINE



## POTENCIA

Motor	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas
Cilindrada	812cc
Par motor máximo	48.0 lb-ft @ 3,500 rpm
Diámetro por carrer	72.0 x 66.5mm
Relación de compresión	9.5:1
Sistema de combustible	DFI® with 34mm throttle body
Transmisión	Continuously Variable Transmission (CVT) with (H,L,N,R)
Transmisión final	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Frenado del motor	Yes
Alternator Output (max)	75 amp

Frenos traseros	Dual disc, 1-piston caliper
Distancia al suelo	10.2 in
Depósito de combustible	7.9 gal
Radio de giro	16.0 ft
Dimensiones de la plataforma de carga (L x An x Al)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Capacidad de la plataforma de carga	999 lb (3-person)/350 lb (6-person)/348 lb CA Model
Capacidad de carga útil	1,616.3/1,263.5 lb CA Model
Asientos	3-person (1 row), 6 person (2 row)
Capacidad de remolque	2,000 lb
Faros	(2) Halogen headlights

## CAPACIDAD

Suspensión delantera / recorrido del neumático	Double wishbone/8.7 in
Suspensión trasera / recorrido del neumático	Double wishbone/8.5 in (L)/8.7 in (R)
Neumáticos delanteros	26 x 9-12, radial
Neumáticos traseros	26 x 11-12, radial
Wheel Type	Steel
Dirección	Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering
Tipo de freno de estacionamiento	Independent, mechanical disc
Frenos delanteros	Dual disc, 2-piston caliper

## DETALLES

Largo total	133.3 in
Ancho total	64.0 in
Altura total	77.6 in
Dry Weight	1,832.4/1,834.6 lb** CA Model
Peso en orden de marcha	1,911.7/1,913.9 lb* CA Model
Distancia entre ejes	92.3 in
Instrumental	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps
Colores disponibles	Timberline Green
Garantía	Garantía limitada Kawasaki Strong de 3 años

Escanear con cámara para ver videos, características clave y más.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
 \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
 All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.  
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visite [Kawasaki-la.com](http://Kawasaki-la.com) para obtener detalles completos del producto.