

2025

# NINJA H2<sup>®</sup>R ABS

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



NEGRO MIRROR COATED MATTE SPARK



## POTENCIA

<b>Motor</b>	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
<b>Cilindrada</b>	998cc
<b>Diámetro por carrera</b>	76.0 x 55.0mm
<b>Relación de compresión</b>	8.3:1
<b>Maximum Horsepower</b>	321.5 hp <sup>1</sup> @ 14,000 rpm
<b>Par motor máximo</b>	121.5 lb-ft @ 12,500 rpm
<b>Sistema de combustible</b>	DFI <sup>®</sup> with 50mm throttle bodies (4) with dual injection; Kawasaki Supercharger
<b>Encendido</b>	TCBI with Digital Advance
<b>Transmisión</b>	6-speed, return shift, dog-ring
<b>Transmisión final</b>	Sealed chain
<b>Asistencia electrónica para el piloto</b>	Economical Riding Indicator, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), IMU-Enhanced Chassis Orientation Awareness, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper

## RENDIMIENTO

<b>Suspensión delantera/recorrido del neumático</b>	43mm inverted Kayaba AOS-II fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in
<b>Suspensión trasera/recorrido del neumático</b>	Uni-Trak <sup>®</sup> , Öhlins TTX36 gas-charged shock with piggyback reservoir, 30-way compression and rebound damping adjustability, 16-way spring preload adjustability, and top-out spring/5.3 in

<b>Neumático delantero</b>	120/60-17 V01F slick
<b>Neumático trasero</b>	190/65-17 V01R slick
<b>Frenos delanteros</b>	Dual 330mm semi-floating discs with dual radial-mount, opposed 4-piston Brembo M50 Monobloc calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
<b>Frenos traseros</b>	Single 250mm disc with opposed 2-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

## DETALLES

<b>Tipo de chasis</b>	Trellis, high-tensile steel, with swingarm mounting plate
<b>Ángulo de dirección/Avance</b>	25.1° / 4.3 in
<b>Largo total</b>	81.5 in
<b>Ancho total</b>	33.5 in
<b>Altura del asiento</b>	45.7 in
<b>Distancia al suelo</b>	5.1 in
<b>Altura del asiento</b>	32.7 in
<b>Dry Weight</b>	432.2 lb**
<b>Peso en orden de marcha</b>	476.3 lb*
<b>Depósito de combustible</b>	4.5 gal
<b>Distancia entre ejes</b>	57.1 in
<b>Características especiales</b>	Supercharged engine, Carbon fiber aerodynamic downforce generating devices, Highly Durable Paint
<b>Colores disponibles</b>	Mirror Coated Matte Spark Black
<b>Garantía</b>	N/A

Escanear con cámara para ver videos, características clave y más.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visite [Kawasaki-la.com](http://Kawasaki-la.com) para obtener detalles completos del producto.